



EL80 Notebook PC

Intel® Core™2 Duo processor Ready!!



Ordering Information

| Model Name | Product Code | Note |
|------------|--------------|-------------------|
| EL80 | CEL80945PM1 | Discrete Graphics |

Specification

| | |
|------------------------|--|
| Processor | <ul style="list-style-type: none"> ■ Intel® Core™ Duo Processor with 2MB On-Die L2 Cache (T1300, T2300, T2300E, T2400, T2500, T2600, T2700) ■ Intel® Celeron® M Processor (Core Duo based) 1M On-Die L2 Cache speeds from 1.5+ GHz. ■ Intel® Core™ 2 Duo, 667MHz FSB, 4M L2Cache, 1.66GHz (T5500) up to 2.33GHz (T7600) uFC-PGA Package |
| BIOS | <ul style="list-style-type: none"> ■ 1024KB Flash BIOS ROM |
| Chipset | <ul style="list-style-type: none"> ■ Intel® 945PM + ICH7-M ■ 533/667 MHz FSB support |
| Main Memory | <ul style="list-style-type: none"> ■ Zero on board memory and two SO-DIMM with 512MB/1GB modules ■ 256MB to maximum 2GB 533/667MHz DDR2 ■ Easy upgrade from bottom side for two SODIMM |
| ODD | <ul style="list-style-type: none"> ■ Fixed 12.7mm height ■ Combo(CD-RW/DVD-ROM) (24x/24x/8x/24x) <ul style="list-style-type: none"> ◆ DVD-RAM/-R/-RW readable ■ DVD Super-Multi (DVD-RAM/-R/-RW/+R/+RW) <ul style="list-style-type: none"> ◆ 8X write ◆ Support Double-Layer Recording is required |
| LCD Display (CBB*) | <ul style="list-style-type: none"> ■ Support 15.4" WXGA(1280x800), anti-glare and anti-reflection |
| Graphics Chip | <ul style="list-style-type: none"> ■ NVIDIA G73M ■ G73M with 256MB(16M16x8) ■ Core/MEM clock for G73M is 350MHz/350MHz, TDP 15.94W(12.1W GPU/3.84W Memory) |
| Hard Disk Drive (CBB*) | <ul style="list-style-type: none"> ■ 9.5mm, 2.5" S-ATA HDD support with 40/60/80/100GB (5400rpm) capacity ■ Easily removable no more than two screws |
| Modem | <ul style="list-style-type: none"> ■ Internal Modem with MDC 1.5 solution <ul style="list-style-type: none"> ◆ V.92/56K bps; V.90/56K bps |

| | |
|--|--|
| LAN & WLAN & Bluetooth (Option) & Camera | <ul style="list-style-type: none"> ■ Realtek 8111B for Giga bit LAN ■ 802.11b/g, a/b/g via Mini-Card interface ■ Bluetooth interface for USB2.0 ■ 1.3M Pixel CMOS via USB2.0 interface |
| Audio | <ul style="list-style-type: none"> ■ Realtek ALC883 ■ HD Audio ■ Microphone-in and headphone-out ■ Internal Microphone ■ Two stereo speakers ■ Volume control: Hot-key control for XP |
| PCMCIA | <ul style="list-style-type: none"> ■ ENE CB714 controller ■ PC card 95 supported with 1x Type II ■ PCI – Express card (54mm type) x1 |
| Keyboard (CBB*) | <ul style="list-style-type: none"> ■ 85/86 keys support with 101/102 key emulation without stick-point. ■ Windows key, Application key ■ Standard pitch, 3.0mm travel length. ■ Multi-Langue support. |
| Pointing Device | <ul style="list-style-type: none"> ■ Touch Pad with two buttons |
| Memory card reader | <ul style="list-style-type: none"> ■ 3-in-1 Flash Card Reader (SD/MMC/MS) |
| IEEE 1394 | <ul style="list-style-type: none"> ■ VIA VT6311S. ■ PCI single chip solution, PCI 2.2 compliant. ■ OHCI v1.1 ■ IEEE1394.A 4-pin |
| Interface I/O Port | <ul style="list-style-type: none"> ■ 3 USB (V2.0, horizontal type, 2 in Right side, 1 in Left side) ■ 1 RGB; VGA port, 15pins (Right side) ■ 1 S-Video out (Rear side) ■ 1 Microphone-in (Right side) ■ 1 Headphone-out with S/PDIF jack (Right side) ■ 1 DC-in jack(Rear side) ■ 1 RJ-11 jack for 56Kbps V.90/92 Modem(Rear side) ■ 1 RJ-45 jack (Left side) ■ 1 Kensington lock (Rear side) ■ 1 ExpressCard/54 (Left side) ■ 1 PCMCIA Type II (Left side) ■ 1 3-in-1 Flash Card Reader(SD/MMC/MS) (front side) ■ 1 IEEE 1394 (4-pin, left side) ■ Two way communication switch (Left to off, Right to on) ■ Internal microphone x 1 (in LCD module) ■ Color-coded connectors |
| System Status LED Button | <ul style="list-style-type: none"> ■ 3 K/B indicators: Caps Lock(Green), and Num Lock(Green), Scroll Lock(Green) ■ 1 Power Button LED(Green) ■ 1 LED for IDE HDD activity (Green) ■ 1 LED for System status (Power On / Suspend) (Green) ■ 1 LED for Battery status (Charging / Full / L1 / L2) (Green / Amber) ■ 1 LED for Wireless Card (Amber) ■ 1 LED for Memory card accessing (Green) ■ Wireless LAN Led status <ul style="list-style-type: none"> ◆ Kill switch on: Slow blink ◆ Searching: Fast blink ◆ Connection: On ◆ File transfer: Fast blink |
| Controls | <ul style="list-style-type: none"> ■ Power button (support software off, 4 sec)x 1 ■ Magnetic lid switch control for system standby/wakeup or suspend/resume ■ One Switch to On/Off Wireless Device for wireless control |
| User Keys | <ul style="list-style-type: none"> ■ Control button for short-Cut key functions <ul style="list-style-type: none"> ◆ 1 Internet (Explorer) key ◆ 1 E-mail (Outlook) key ◆ 2 User Define Key |

| | |
|----------------------------|--|
| AC adapter (CBB*) | <ul style="list-style-type: none"> ■ Universal AC adapter. 90-264V AC, 47-63HZ <ul style="list-style-type: none"> ◆ 90W with 19V DC ◆ 3 pin 240V AC cable |
| Battery Pack & Life (CBB*) | <ul style="list-style-type: none"> ■ 6 cell LI-ION of 18650 size battery pack .(10.8V x 4800mAh) |
| Software | <ul style="list-style-type: none"> ■ Phoenix First BIOS ■ Suspend to RAM/Disk ■ No support APM ■ Security: Power-On Password, Supervisor Password, HDD password ■ USB memory Boot support ■ Support SMBIOS 2.3, PCI2.2. ■ ACPI 2.0 compliance with Intel Speed-step Support C1, C2, C3, C4 and S3, S4 for mobile CPU ■ DMI utility for BIOS serial number configurable/asset tag ■ Support PXE ■ Wake on LAN from S3 ■ Wake on LAN form S4 in AC mode |
| Dimensions/Weight | <ul style="list-style-type: none"> ■ Dimensions : 362(W)x265(D)x31.7(H)mm, 38.9mm in rear side ■ Weight: <ul style="list-style-type: none"> ◆ Less than 2.8Kg with 15.4"WXGA & 6cell battery |
| OS | <ul style="list-style-type: none"> ■ Windows XP HE(SP2), ■ Windows XP Pro(SP2)(with PC 2001 LOGO, and K/B LOGO) ■ Windows Vista design ready |
| Mini Card | <ul style="list-style-type: none"> ■ One Mini card slot for WLAN |
| Security | <ul style="list-style-type: none"> ■ HDD Password ■ Fingerprint(Optional) ■ Kensington lock |
| Regulatory | <ul style="list-style-type: none"> ■ EMI: FCC-B, CE, CCC, A,C-Tick, VCCI, BSMI ■ Safety: Compliant to UL/CSA, TUV, CB ■ PTT: FCC-Part 68, CTR 21 ■ MDA2005 Compliant ■ Energy Star ■ WHQL LOGO |
| Environment | <ul style="list-style-type: none"> ■ Temperature: <ul style="list-style-type: none"> ◆ Operating: 5 - 35°C ◆ Storage: -20 - 65°C ■ Humidity: <ul style="list-style-type: none"> ◆ 10 - 90% without condensation. ■ Altitude: <ul style="list-style-type: none"> ◆ Operating sea level up to 10,000 ft ◆ Storage sea level up to 40,000 ft |

*Common Building Blocks (www.intel.com/go/interchange)